



SPECIFICATION SHEET

C2402 Snell PU Coated EN388 Level D Cut-Resistant Glove



Technical Data

Material	HPPE/steel fiber/polyester
Cuff	Seamless knitting
Coating	PU
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	10000 pairs
Production Leadtime	45 days

Performance

EN388:2016: 3X43D
ANSI A4

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Blends smooth and steel fibers for enhanced cut performance
- ◆ Premium polyurethane palm coating can survive over 30,000 abrasive cycles
- ◆ Fits the natural contours of the hand, which improves dexterity for precision handling tasks
- ◆ All-black design that hides dirt and grime
- ◆ Elasticated knitted wrist ensures a secure fit and keeps hands free of dust ingress

Applications

- ◆ Assembly
- ◆ Builders
- ◆ Brick Handling
- ◆ Construction
- ◆ DIY
- ◆ Fabrication
- ◆ Glass manufacturing
- ◆ Industrial work
- ◆ Maintenance
- ◆ Metal handling
- ◆ Railway Maintenance
- ◆ Scaffolding