



SPECIFICATION SHEET

C2404 Snell Black PU Coated Cut-Resistant Glove Cut F



Technical Data

Material	HPPE/Steel
Cuff	Seamless knitting
Coating	PU
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	8000 pairs
Production Leadtime	50 days

Performance

EN388:2016: 4X43F
ANSI A6

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Comfortable 13-gauge liner ensures a lighter and comfortable feel to the hands
- ◆ Exceptional grip for working in dry conditions
- ◆ PU coated palms ensure high dexterity for the wearer
- ◆ Steel reinforcement for overall strength and durability
- ◆ Maximum level F cut-protection for high-risk cut hazards
- ◆ Maximum level 4 abrasion, tear resistance

Applications

- ◆ Automotive
- ◆ Building and Construction
- ◆ Glass
- ◆ Product Protection
- ◆ Steel and Metal
- ◆ Waste
- ◆ Recycling