



SPECIFICATION SHEET

C2410 Snell Flat Nitrile Cut Resistant Gloves-Cut C



Technical Data

Material	Hppe/glass fiber/polyester
Cuff	Seamless knitting
Coating	Flat nitrile
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	8000 pairs
Production Leadtime	45 days

Performance

EN388:2016: 4X42C

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Seamless knit construction provides comfort & dexterity
- ◆ 13 Gauge liner provides high tensile strength
- ◆ Nitrile smooth coating is resistant to liquids, proving a very tacky dry grip for specific applications that require secure holding power
- ◆ Knit Wrist helps prevent dirt and debris from entering the glove
- ◆ Launderable for extended life and to reduce replacement costs

Applications

- ◆ Material handling
- ◆ Glass handling operations
- ◆ Fishing industries
- ◆ General maintenance
- ◆ Wood working
- ◆ Waste handling
- ◆ Recycling