



SPECIFICATION SHEET

C2412 Snell Nitrile Sandy High Cut Resistant Glove-Cut E



Technical Data

Material	Hppe/steel/glass fiber/ polyester/spandex
Cuff	Seamless knitting
Coating	Sandy nitrile
Coating Coverage	Palm & fingers, Thumb reinforced
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	10000 pairs
Production Leadtime	45-55 days

Performance

EN388:2016: 4X43E
ANSI A5

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Sandy nitrile coating for superior durability
- ◆ Exceptional dexterity and comfort
- ◆ Breathable fabric and product design
- ◆ Long knit cuff for a more secure fit
- ◆ Thick coating with great grip and enhances the lifetime
- ◆ EN Cut Level D

Applications

- ◆ Automotive
- ◆ Construction
- ◆ Engineering
- ◆ Glass handling
- ◆ Recycling
- ◆ Railway maintenance
- ◆ Transportation
- ◆ Utilities