



SPECIFICATION SHEET

C2413 Snell Nitrile Foam Sandy Cut Resistant Glove-Cut D



Technical Data

Material	Hppe/steel/polyester
Cuff	Seamless knitting
Coating	Sandy nitrile
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	10000 pairs
Production Leadtime	45-55 days

Performance EN388:2016: 4X43D ANSI A4

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ 13 gauge seamless liner is lightweight & breathable
- ◆ Providing good dexterity & flex to reduce hand fatigue
- ◆ The sandy nitrile palm coating is resistant to oils and grease
- ◆ Gives exceptional grip in dry, wet and oily environments.
- ◆ Excellent abrasion and tear properties

Applications

- ◆ Automotive
- ◆ Automotive Aftermarket
- ◆ Assembly
- ◆ Metal Fabrication
- ◆ Railway Maintenance
- ◆ Glass Handling
- ◆ Construction
- ◆ General Maintenance
- ◆ Recycling