



C2414 Snell Cut Protection Glove for Oily Environments



Product Features

- ◆ 13 gauge seamless liner is lightweight & breathable
- ◆ Double nitrile coating, first with flat nitrile half coated, second with foam nitrile on palm & fingers & thumb makes the high durability
- ◆ The sandy nitrile palm coating is resistant to oils and grease
- ◆ Gives exceptional grip in dry, wet and oily environments.
- ◆ Excellent abrasion and tear properties
- ◆ Withstands contact heat up to 100°C

Technical Data

Material	Hppe/nylon/spandex
Cuff	Seamless knitting
Coating	Sandy nitrile
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	10000 pairs
Production Leadtime	45-55 days

Performance

EN388:2016: 4X43B
ANSI A2

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Applications

- ◆ Automotive
- ◆ Assembly
- ◆ Metal Fabrication
- ◆ Railway Maintenance
- ◆ Construction
- ◆ General Maintenance
- ◆ Machine operating