



SPECIFICATION SHEET

C2415 Snell Cut Glove with Nitrile Coated E Level



Product Features

- ◆ Seamless construction offers increased comfort and breathability
- ◆ The blended shell is lightweight & provides excellent dexterity & cut resistance
- ◆ Nitrile Micro Surface coatings are impermeable providing an elevated grip in dry and oily conditions
- ◆ Knit Wrist helps prevent dirt and debris from entering the glove
- ◆ Washable, resistant to chemicals, water, and ultraviolet light

Technical Data

Material	Hppe/steel/nylon
Cuff	Seamless knitting
Coating	Sandy nitrile
Coating Coverage	Palm & fingers
Gauge	18
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	8000 pairs
Production Leadtime	45-55 days

Performance

EN388:2016: 4X43E
ANSI A5

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Applications

- ◆ Automotive
- ◆ Assembly
- ◆ Metal Fabrication
- ◆ Railway Maintenance
- ◆ Construction
- ◆ General Maintenance
- ◆ Machine operating