



SPECIFICATION SHEET

C2418 Snell Touchable PU Coated Cut Protective Glove



Technical Data

Material	HPPE/steel/nylon/elasthane
Cuff	Seamless knitting
Coating	PU
Coating Coverage	Palm & fingers
Gauge	15
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	10000 pairs
Production Leadtime	45-50 days

Performance

EN388:2016: 4X42D

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ EN388 cut level D can take high risk
- ◆ 15 gauge seamless knitting construction offers the fitness
- ◆ Palm coated PU with great grip and abrasion resistance, the fingers with compatible function, it is unnecessary to take off the gloves when works
- ◆ Extended thumb crotch reinforcement to make the gloves more durable

Applications

- ◆ Assembly
- ◆ Builders
- ◆ Brick handling
- ◆ Construction
- ◆ DIY
- ◆ Fabrication
- ◆ Glass manufacturing
- ◆ Industrial work
- ◆ Maintenance
- ◆ Metal handling
- ◆ Railway maintenance
- ◆ Light oil works