



**SPECIFICATION SHEET**

**C2421 Snell Cut Protection Glove with Nitrile Foam Coating- Cut D**



**Technical Data**

Material	Hppe/steel/glass/nylon/spandex
Cuff	Seamless knitting
Coating	Sandy nitrile
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	8000 pairs
Production Leadtime	45-55 days

**Product Features**

- ◆ Cut level D designed to protect high risk.
- ◆ The sandy nitrile coating is resistant to oils and grease.
- ◆ Gives exceptional grip in dry, wet and oily environments.
- ◆ The comfortable sandy nitrile coating offers maximum abrasion and tear protection.
- ◆ The double nitrile coating offers extra protection when handling abrasive material and increases the life of the glove.

**Performance**

EN388:2016: 4X42D  
ANSI A6

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

**Applications**

- ◆ Aerospace
- ◆ Automotive
- ◆ Construction
- ◆ Engineering
- ◆ Glass handling
- ◆ Railway maintenance
- ◆ Transportation