



## SPECIFICATION SHEET

### C2422 Snell Sandy Nitrile Double Dipped Cut Resistant Grip Glove



#### Technical Data

Material	Hppe/steel/nylon
Cuff	Seamless knitting
Coating	Sandy foam nitrile
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	8000 pairs
Production Leadtime	45-55 days

#### Product Features

- ◆ Cut resistant level D (equiv cut resistance level 5)
- ◆ Excellent abrasion and tear resistance
- ◆ Resistant to oils and grease
- ◆ Elasticated wrist
- ◆ Dual dipped offers excellent grip and extends the lifetime of the gloves

#### Performance

EN388:2016: 4X42D  
ANSI A4

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

#### Applications

- ◆ Aerospace
- ◆ Automotive
- ◆ Construction
- ◆ Engineering
- ◆ Glass handling
- ◆ Recycling
- ◆ Railway maintenance
- ◆ Transportation
- ◆ Utilities