



### C2423 Snell Cut Protection A5 Level E Work Glove



#### Product Features

- ◆ Sandy foam nitrile palm coating provides a strong grip in both wet and dry applications.
- ◆ Padded Palm.
- ◆ The sandy nitrile coating is resistant to oils and grease.
- ◆ The comfortable sandy nitrile coating offers maximum abrasion and tear protection.
- ◆ The 13 gauge high performance glove is ideal for applications needing high cut and abrasion resistance.

#### Technical Data

Material	Hppe/polyester/steel/basalt/spandex
Cuff	Seamless knitting
Coating	Sandy foam nitrile
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	8000 pairs
Production Leadtime	45-55 days

#### Performance

EN388:2016: 4X42E  
ANSI A5

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

#### Applications

- ◆ Automotive
- ◆ Metal Fabrication
- ◆ Construction
- ◆ Petrochem Industry
- ◆ General Assembly
- ◆ Glass Cutting
- ◆ Sheet Metal Handling
- ◆ Manufacturing
- ◆ Warehousing
- ◆ Material Handling