



SPECIFICATION SHEET

C2424 Snell Basalt Cut Protection A6 Automotive Work Glove



Product Features

- ◆ The blended fibers to make sure the cut level with EN388 E or ANSI A6.
- ◆ Sandy foam nitrile palm coating provides a strong grip in both wet & dry applications.
- ◆ Palm with screen touchable function, workers don't need to put off the gloves.
- ◆ The sandy nitrile coating is resistant to oils & grease, suitable for testing, parts assembly & equipment repair.
- ◆ Thumb with Reinforcement for extended durability.

Technical Data

Material	Hppe/polyester/steel/basalt/spandex
Cuff	Seamless knitting
Coating	Sandy foam nitrile
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	8000 pairs
Production Leadtime	45-55 days

Performance

EN388:2016: 4X42E
ANSI A6

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Applications

- ◆ Automotive
- ◆ Metal Fabrication
- ◆ Construction
- ◆ Petrochem Industry
- ◆ General Assembly
- ◆ Glass Cutting
- ◆ Sheet Metal Handling
- ◆ Manufacturing
- ◆ Warehousing
- ◆ Material Handling