



SPECIFICATION SHEET

C2428 Snell Oil Resistant Safety Glove with Nitrile Foam- ANSI A6



Technical Data

Material	Hppe/Steel/ polyester
Cuff	Seamless knitting
Coating	Double nitrile foam sandy
Coating Coverage	¾ palm & fingers
Gauge	13
Logo printing	Heat transfer
Sizes	7-11
MOQ	8000 pairs
Production Leadtime	45-55 days

Performance

EN388:2016: 4X43E
ANSI A6

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Double coating offers oil & grease resistance.
- ◆ Gives exceptional grip in dry, wet conditions.
- ◆ The comfortable sandy nitrile coating offers maximum abrasion and tear protection.
- ◆ Elasticated cuff for exacting & comfortable fit.
- ◆ A6 cut level suitable for the high risk hazards.

Applications

- ◆ Automotive
- ◆ Component assembly
- ◆ Construction
- ◆ Utilities
- ◆ Maintenance & repairs
- ◆ Gardening
- ◆ Glass industry
- ◆ Mining
- ◆ Metal Fabrication