



SPECIFICATION SHEET

C2434 Snell Cut Resistant Arm Protection Wristband



Technical Data

| | |
|---------------------|----------------------|
| Material | Diamond fiber |
| Cuff | Knitted |
| Coating | None |
| Coating Coverage | None |
| Gauge | 10 |
| Logo printing | Ink or heat transfer |
| Sizes | 15cm or personalized |
| MOQ | 2000 pairs |
| Production Leadtime | 50 days |

Performance

EN388:2016: X4XD

| | | | | | | |
|---------------|---|---|---|---|---|---|
| Abrasion | 0 | 1 | 2 | 3 | 4 | |
| Cut | X | 1 | 2 | 3 | 4 | 5 |
| Tear | 0 | 1 | 2 | 3 | 4 | |
| Puncture | 0 | 1 | 2 | 3 | 4 | |
| Cut (TDM-100) | A | B | C | D | E | F |

Product Features

- ◆ Seamless knitting, lightweight design
- ◆ No distinction between left and right hands, easy and convenient to wear
- ◆ Diamond cut resistant liner offers cut level 4 to protect your wrist safe
- ◆ Can still be used after washing, reducing usage costs
- ◆ Easily to be taken

Applications

- ◆ Glass fabrication
- ◆ Automotive industry
- ◆ Construction and mining
- ◆ Telecom
- ◆ Public works
- ◆ Metal handling
- ◆ Maintenance
- ◆ Agriculture
- ◆ Logistic
- ◆ Warehouse