

Qingdao Snell Safety Dedicated to Security

SPECIFICATION SHEET

C2438 Snell Cut Resistant Foam Nitrile Safety Grip Glove



Product Features

- ◆ The sandy nitrile coating is resistant to oils and grease.
- Gives exceptional grip in dry, wet and oily environments.
- ◆ The comfortable sandy nitrile coating offers maximum abrasion and tear protection.
- ◆ Knit wrist helps prevent dirt and debris from entering the glove

Technical Data	
Material	Hppe/glass fiber/polyester
Cuff	Seamless knitting
Coating	Foam sandy nitrile
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	10000 pairs
Production Leadtime	45-55 days

Performance	EN388:2016: 4X42C ANSI A3						
Abrasion	0	1	2	3	4		
Cut	X	1	2	3	4	5	
Tear	0	1	2	3	4		
Puncture	0	1	2	3	4		
Cut (TDM-100)	Α	В	С	D	Ε	F	

Applications

- Aerospace
- Automotive
- ◆ Construction
- ◆ Engineering
- Glass handling
- ◆ Railway maintenance
- **♦** Transportation

Tel: +86 17205448906 | sales@snellsafety.com