



C2441 Snell Black Sandy Foam Coating Cut Resistant Grip Glove



Technical Data

Material	Hppe/polyester/nylon/steel/spandex
Cuff	Seamless knitting
Coating	Sandy foam nitrile
Coating Coverage	Palm & fingers
Gauge	
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	6000 pairs
Production Leadtime	45-55 days

Product Features

- ◆ Seamless construction offers increased comfort and breathability.
- ◆ The shell is lightweight & provides excellent dexterity.
- ◆ The comfortable sandy nitrile coating offers maximum abrasion and tear protection.
- ◆ The sandy nitrile coating is resistant to oils and grease.
- ◆ Cut level D designed to protect high risk.

Performance

EN388:2016: 4X43D
ANSI A4

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Applications

- ◆ Automotive
- ◆ Metal Fabrication
- ◆ Construction
- ◆ Parts cleaning
- ◆ General Assembly
- ◆ Mechanical equipment maintenance
- ◆ Sheet Metal Handling
- ◆ Manufacturing
- ◆ Warehousing
- ◆ Material Handling