



## SPECIFICATION SHEET

### C2448 Snell PU Cut Resistant EN388 D Assembly Glove



#### Technical Data

Material	HPPE/glass fiber/ steel/nylon
Cuff	Seamless knitting
Coating	PU
Coating Coverage	Palm & fingers
Gauge	15
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	10000 pairs
Production Leadtime	45-50 days

#### Performance

EN388:2016: 4X43D  
ANSI A6

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

#### Product Features

- ◆ Hppe & steel blended liner offers great protection for hands
- ◆ Flexible polyurethane palm coating provides superior grip and abrasion resistance
- ◆ Elastic knit wrist helps prevent dirt and debris from entering the glove
- ◆ Seamless construction for enhanced comfort and breathability
- ◆ Grey shell color is stain resistant
- ◆ A6 cut level or EN388 D level offers high risk protection

#### Applications

- ◆ Assembly
- ◆ Automotive
- ◆ Engineering
- ◆ Glass manufacture
- ◆ Logistics
- ◆ Maintenance
- ◆ Mechanics
- ◆ Aerospace industry
- ◆ Metal fabrication
- ◆ Metal Recycling