



**C2502 Snell Nitrile Foam Coated Assembly Gloves Cut C**



**Technical Data**

Material	Hppe/nylon/spandex
Cuff	Seamless knitting
Coating	Sandy foam nitrile
Coating Coverage	Palm & fingers
Gauge	18
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	6000 pairs
Production Leadtime	45-55 days

**Product Features**

- ◆ Lightweight feel promotes
- ◆ Foam nitrile palm coating enhances grip strength and stability
- ◆ Thick seamless knitting cuff prevents dirt and debris from entering the glove
- ◆ Level C cut resistance under EN 388
- ◆ Available in five different sizes for a guaranteed fit

**Performance**

**EN388:2016: 4X42C**  
**ANSI A3**

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

**Applications**

- ◆ Automotive
- ◆ Builders/Construction
- ◆ DIY
- ◆ Fabrication
- ◆ Glass Manufacture
- ◆ Machine Operation
- ◆ Maintenance
- ◆ Mechanic
- ◆ Packaging/Packing
- ◆ Precise Handling Applications
- ◆ Warehouse
- ◆ Woodworking