

Qingdao Snell Safety Dedicated to Security

SPECIFICATION SHEET

C2503 Snell E Level Cut Protective Nitrile Foam Oil Grip Glove



Product Features

- Cut E level cut resistance prevents cuts when handling sharp materials
- Nitrile foam on palms and fingers provides high grip in oily, wet and dry conditions
- ◆ Steel & Hppe blended shell ensures the cut protection
- Provides maximum level 4 abrasion and tear resistance
- Lightweight and flexible design prevents hand fatigue
- Thumb crotch enhances the durability

Technical Data	
Material	Hppe/steel/spandex
Cuff	Seamless knitting
Coating	Foam nitrile
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	6000 pairs
Production Leadtime	45-55 days

Performance	EN388:2016: 4X42E ANSI A6						
Abrasion	0	1	2	3	4		
Cut	Χ	1	2	3	4	5	
Tear	0	1	2	3	4		
Puncture	0	1	2	3	4		
Cut (TDM-100)	Α	В	С	D	E	F	

Applications

- Glass
- ◆ Steel/Metal
- Building/Construction
- Automotive
- Engineering
- Oil •
- Gas/Mining
- Aerospace
- Manufacturing
- Waste
- Recycling

Tel: +86 17205448906 | sales@snellsafety.com