



## SPECIFICATION SHEET

### C2505 Snell D Level Cut Protective Nitrile Foam Oil Grip Glove



#### Technical Data

Material	HPPE/Diamond
Cuff	Seamless knitting
Coating	Foam nitrile
Coating Coverage	Palm & fingers
Gauge	15
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	8000 pairs
Production Leadtime	50-55 days

#### Product Features

- ◆ Cut resistant glove made purely from cut resistant fibers
- ◆ Level D cut resistance for handling sharp edges
- ◆ With no glass or stainless steel fiber glove, with good hand feeling but high cut resistance
- ◆ High abrasion resistance and good tear resistance for longevity
- ◆ 15-gauge liner is thin to provide fantastic dexterity

#### Performance

EN388:2016: 4X42D  
ANSI A4

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

#### Applications

- ◆ Glass
- ◆ Steel/Metal
- ◆ Building/Construction
- ◆ Automotive
- ◆ Engineering
- ◆ Oil
- ◆ Gas/Mining
- ◆ Aerospace
- ◆ Manufacturing
- ◆ Waste
- ◆ Recycling