

Qingdao Snell Safety Dedicated to Security

SPECIFICATION SHEET

12401 Snell Nitrile Foam Cut Resistant and TPR Impact Protection Glove



Product Fe	eatures
------------	---------

- ◆ High performance polyethylene (HPPE) fiber shell is light-weight and provides excellent dexterity & cut resistance.
- ◆ Thermoplastic rubber (TPR) molded finger & back of hand guards for maximum protection.
- Sandy nitrile coating for superior durability.
- Resistant to oils and grease.

Technical Data				
Material	НРРЕ			
Cuff	Seamless knitting			
Coating	Nitrile sandy			
Coating Coverage	Palm & fingers			
Gauge	13			
Impact Coverage	Fingers & back of hand			
Sizes	8-11			
MOQ	6000 pairs			
Production Leadtime	50-60 days			

EN388:2016: 4X43BP ANSI A2						
0	1	2	3	4		
X	1	2	3	4	5	
0	1	2	3	4		
0	1	2	3	4		
Α	В	С	D	Е	F	
	0 X 0 0	0 1 X 1 0 1 0 1	0 1 2 X 1 2 0 1 2 0 1 2	0 1 2 3 X 1 2 3 0 1 2 3 0 1 2 3	ANS 0 1 2 3 4 X 1 2 3 4 0 1 2 3 4 0 1 2 3 4	

Applications

- Construction
- Auto repair
- Mining
- ◆ Metal fabrication
- ◆ Furniture manufacturing

Tel: +86 17205448906 | sales@snellsafety.com