



SPECIFICATION SHEET

I2402 Snell Cut Resistant Impact Gloves with a TPR Design



Product Features

- ◆ High performance polyethylene (HPPE) fiber shell is light-weight & provides excellent dexterity & cut resistance.
- ◆ MicroSurface nitrile-coated padded palm for enhanced wet & dry grip.
- ◆ Thermoplastic rubber (TPR) molded finger, thumb and back of hand guards for maximum protection.
- ◆ Reinforced leather between thumb and index finger.
- ◆ Palm with sandy nitrile coating offers the oil & grease.
- ◆ Hook and loop closure for easy on/off and a secure fit.

Technical Data

Material	HPPE
Cuff	Seamless knitting
Coating	Nitrile sandy
Coating Coverage	Palm & fingers
Gauge	13
Impact Coverage	Fingers & back of hand
Sizes	8-11
MOQ	6000 pairs
Production Leadtime	50-60 days

Performance

EN388:2016: 4X43DP
ANSI A4

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Applications

- ◆ Construction
- ◆ Auto repair
- ◆ Mining & gas
- ◆ Metal fabrication
- ◆ Furniture manufacturing
- ◆ Machinery and equipment
- ◆ Warehousing