

Qingdao Snell Safety Dedicated to Security

SPECIFICATION SHEET

12406 Snell Nitrile Foam Sandy TPR Impact Resistant Glove



Technical Data	
Material	Polyester
Cuff	Seamless knitting
Coating	Nitrile foam sandy
Coating Coverage	Palm & fingers
Gauge	13
Impact Coverage	Fingers & back of hand
Sizes	7-11
MOQ	10000 pairs
Production Leadtime	50-60 days

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	Α	В	С	D	Ε	F

EN388:2016: 3131XP

Product Features

- ◆ 13 gauge polyester shell provides the good dexterity.
- ◆ MicroSurface nitrile-coated palm enhances the grip in the wet & oil conditions.
- ◆ Thermoplastic rubber (TPR) molded finger, thumb and back of hand guards for maximum protection.
- ◆ Thumb with leather reinforced to make the gloves more durable.
- ◆ Hook and loop closure for easy on/off and a secure fit.
- ◆ Hi-Vi color is easily to be seen.

Applications

Performance

- Construction
- Auto repair
- ◆ Furniture manufacturing
- Machinery and equipment
- Warehousing
- ◆ Glass handling
- Agriculture
- Loading and hauling