

Qingdao Snell Safety Dedicated to Security

SPECIFICATION SHEET

12410 Snell Nitrile Foam Grip TPR Cut Impact Resistant Coated Glove



- ◆ High performance polyethylene (HPPE) fiber shell is light-weight & provides excellent dexterity & cut resistance.
- ◆ MicroSurface nitrile-coated padded palm for enhanced wet & dry grip.
- ◆ Thermoplastic rubber (TPR) molded the whole back of hand and fingers to make sure maximum safety protection.
- ◆ Palm with sandy finishing prevents the oil & grease.
- ◆ Reinforced between thumb and index finger enhances the lifetime.
- ◆ Hook and loop closure for easy on/off and a secure fit.

Technical Data	
Material	HPPE/steel
Cuff	Seamless knitting
Coating	Nitrile foam sandy
Coating Coverage	Palm & fingers
Gauge	13
Impact Coverage	Fingers & back of hand
Sizes	8-11
MOQ	6000 pairs
Production Leadtime	50-60 days

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	Α	В	C	D	Е	F

EN388:2016: 4X43EP

ANSI A6

Applications

Performance

- Metal fabrication
- Mining & gas, oilfield
- ◆ Auto repair & assembly
- Machinery and equipment
- **♦** Construction
- Furniture manufacturing
- Warehousing
- ◆ Forestry