



SPECIFICATION SHEET

I2416 Snell A5 Cut Resistant Impact Grip Sandy Glove



Technical Data

Material	HPPE/Steel
Cuff	Seamless knitting
Coating	Nitrile foam sandy
Coating Coverage	Palm & fingers
Gauge	18
Impact Coverage	Fingers & back of hand
Sizes	8-11
MOQ	6000 pairs
Production Leadtime	45-55 days

Product Features

- ◆ Heavy-duty impact gloves in nitrile.
- ◆ A5 cut level delivers high cut protection.
- ◆ TPR back-of-hand and finger protection for impact.
- ◆ Sandy Nitrile coating for superior grip in oily applications, increases abrasion resistance and wear.
- ◆ 18 gauge seamless knitting provides excellent dexterity & prevents dirt and debris from entering the glove.

Performance

EN388:2016: 4X43EP
ANSI A5

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Applications

- ◆ Automotive
- ◆ Oil & Gas
- ◆ Metal handling
- ◆ Metal fabrication
- ◆ Industrial manufacturing
- ◆ Construction
- ◆ Equipment maintenance