



### L2451 Snell ¾ Flat Latex Foam Sandy Grip Safety Glove



#### Technical Data

Material	Polyester
Cuff	Seamless knitting
Coating	Latex foam sandy
Coating Coverage	¾ hand & palm
Gauge	13
Logo printing	Ink or heat transfer
Sizes	9-11
MOQ	12000 pairs
Production Leadtime	45 days

#### Performance

EN388:2016: 2131

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

#### Product Features

- ◆ 13-gauge polyester lining enhances dexterity
- ◆ Back side open to make sure the hands dry and breathable
- ◆ Outer palm with latex foam sandy finishing to enhance the excellent grip and absorb the liquids away
- ◆ Inner with ¾ flat latex coating to make hands dry
- ◆ The knitted cuff prevents dirt and debris from entering the glove
- ◆ Machine washable extends the life of the glove

#### Applications

- ◆ Assembly
- ◆ Construction
- ◆ Material handling
- ◆ Refuse handling
- ◆ Landscaping
- ◆ Automotive service
- ◆ Packing work
- ◆ Transportation