



SPECIFICATION SHEET

L2455 Snell Black Latex Crinkle Dry Construction Glove



Technical Data

Material	Polycotton
Cuff	Seamless knitting
Coating	Latex crinkle/textured
Coating Coverage	Palm & fingers
Gauge	10 Gauge 5 Threads(21s)
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	12000 pairs
Production Leadtime	45 days

Performance

EN388:2016: 2132

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Excellent abrasion resistance for impressive durability
- ◆ Thick 10 gauge 5 threads liner offers great mechanical protection
- ◆ Crinkle latex finish enhances grip in all conditions
- ◆ Polycotton liner is cost effective while still making the gloves durable
- ◆ Knitted cuff provides comfort and warmth, and allows for dexterity so the gloves can be worn all day long

Applications

- ◆ Assembly
- ◆ Automotive
- ◆ Building/construction
- ◆ Engineering
- ◆ General handling
- ◆ Industrial work
- ◆ Maintenance
- ◆ Gardening
- ◆ Packaging/Packing
- ◆ Railway maintenance
- ◆ Transportation