



## SPECIFICATION SHEET

### N2413 Snell Jersey Liner 3/4 Nitrile Dipped Glove



#### Technical Data

|                     |                      |
|---------------------|----------------------|
| Material            | Jersey liner         |
| Cuff                | Knitted              |
| Coating             | Nitrile              |
| Coating Coverage    | 3/4 dipped           |
| Gauge               | /                    |
| Logo printing       | Ink or heat transfer |
| Sizes               | 10                   |
| MOQ                 | 12000 pairs          |
| Production Leadtime | 40 days              |

#### Performance

EN388:2016: 2111X

|               |   |   |   |   |   |   |
|---------------|---|---|---|---|---|---|
| Abrasion      | 0 | 1 | 2 | 3 | 4 |   |
| Cut           | X | 1 | 2 | 3 | 4 | 5 |
| Tear          | 0 | 1 | 2 | 3 | 4 |   |
| Puncture      | 0 | 1 | 2 | 3 | 4 |   |
| Cut (TDM-100) | A | B | C | D | E | F |

#### Product Features

- ◆ Nitrile-coated gloves designed for flexibility
- ◆ Pure cotton jersey liner with 3/4 nitrile coating
- ◆ Provide excellent abrasion resistance
- ◆ Breathable open backs for skin ventilation
- ◆ Oil-repellent outer surface
- ◆ Elasticated knitwrist for a snug fit
- ◆ Great alternative to PVC and leather gloves

#### Applications

- ◆ Agricultural
- ◆ Building
- ◆ Construction
- ◆ Machinery /Equipment industries
- ◆ Assembly
- ◆ Factory maintenance
- ◆ Light metal fabrication and handling
- ◆ Metal fabrication
- ◆ Quality control