



SPECIFICATION SHEET

N2419 Snell Nitrile Sandy 3/4 Dipped Oil Resistant Glove



Technical Data

Material	Polyester
Cuff	Seamless knitting
Coating	Nitrile Sandy
Coating Coverage	3/4 dipped
Gauge	13
Logo printing	Ink or heat transfer
Sizes	8-11
MOQ	12000 pairs
Production Leadtime	45 days

Performance

EN388:2016: 4121X

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Double coating of nitrile offers excellent levels of oil and water resistance
- ◆ Nitrile coating improves the grip function
- ◆ Seamless liner ensures optimal comfort during use
- ◆ Breathable design helps to keep hands cool, and minimise sweat build-up
- ◆ Dextrous design enables ease-of-movement, and helps to prevent hand fatigue
- ◆ Excellent level of abrasion resistance for secure handling of coarse or rough materials

Applications

- ◆ Oil and Gas
- ◆ Offshore Oil Work
- ◆ Oil Filtration & Handling
- ◆ Aerospace
- ◆ Automotive
- ◆ Manufacturing
- ◆ General / Manual Handling
- ◆ Warehousing and Logistics
- ◆ Shipping