



### N2421 Snell Flex Nitrile Sandy 3/4 Grip Glove



#### Technical Data

Material	Polyester
Cuff	Seamless knitting
Coating	Nitrile foam sandy
Coating Coverage	Half of hands+ fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	8-11
MOQ	12000 pairs
Production Leadtime	45 days

#### Performance

EN388:2016: 4121X

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

#### Product Features

- ◆ Ideal for precise handling in dry environments
- ◆ ¾ nitrile coating for added grip and protection
- ◆ Mimics the hand at rest to reduce hand fatigue
- ◆ Designed with smooth and rounded fingertips
- ◆ Offers outstanding tactile sensitivity
- ◆ Features a micro-cup finish for more control and grip
- ◆ Double nitrile coating enhances the grip & abrasion resistance

#### Applications

- ◆ Automotive
- ◆ Aerospace
- ◆ Assembly
- ◆ DIY work
- ◆ Glass handling
- ◆ Inspection
- ◆ Logistics
- ◆ Maintenance
- ◆ Packaging
- ◆ Recycling
- ◆ Construction