



SPECIFICATION SHEET

N2438 Snell Nitrile Foam Sandy Grip Green Black Assembly Glove



Technical Data

| | |
|---------------------|----------------------|
| Material | Polyester |
| Cuff | Seamless knitting |
| Coating | Nitrile sandy |
| Coating Coverage | Palm and fingers |
| Gauge | 13 |
| Logo printing | Ink or heat transfer |
| Sizes | 7-11 |
| MOQ | 12000 pairs |
| Production Leadtime | 45 days |

Performance

EN388:2016: 4131X

| | | | | | | |
|---------------|---|---|---|---|---|---|
| Abrasion | 0 | 1 | 2 | 3 | 4 | |
| Cut | X | 1 | 2 | 3 | 4 | 5 |
| Tear | 0 | 1 | 2 | 3 | 4 | |
| Puncture | 0 | 1 | 2 | 3 | 4 | |
| Cut (TDM-100) | A | B | C | D | E | F |

Product Features

- ◆ Sandy-nitrile coated for grip of wet and dry items
- ◆ Palm coated sandy nitrile, with oil and grease resistance
- ◆ Lightweight polyester construction, breathable back offers elasticity & dexterity
- ◆ With great abrasion resistance, suitable for the small parts and precision work

Applications

- ◆ Rail Maintenance
- ◆ Precision work
- ◆ Engineering
- ◆ Automotive
- ◆ Mechanics
- ◆ Construction
- ◆ Building
- ◆ Logistics
- ◆ Packing
- ◆ Electricians
- ◆ Assembly
- ◆ General Use