

## T2401 Snell Pigskin Unlined Leather Driver Work Glove



#### **Product Features**

- Excellent in wet conditions; quick-drying and leather remains soft
- Offers the best breathability
- Stays pliable and flexible with wear
- Excellent price point for a leather work glove
- The wing thumb option provides the best, most natural flow of one's thumb movement.
- Quick-fit cuff design for easy on and off

#### **Technical Data**

Leather Cut	Pigskin
Cuff	Slip-on-open
Leather Color	Yellow
Thumb Type	Wing
Logo	Heat transfer/Label
Sizes	7-11
MOQ	2000 pairs
Production Leadtime	50-60 days

Performance	EN388:2016: 3131X					
Abrasion	0	1	2	3	4	
Cut	Х	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	Α	В	С	D	Е	F

#### **Applications**

- Agriculture
- Construction
- Engineering
- Industrial works
- Mechanical works
- Oil and Gas
- Warehousing & logistics
- Gardening



## T2402 Snell Grain Unlined Cowhide Leather Driver Work Glove Wing Thumb



#### **Product Features**

- Made from sturdy and tough cowhide full grain leather
- Offers outstanding dexterity for handling small objects
- Provides excellent resistance against abrasions, tears and punctures
- The wing thumb option provides the best, most natural flow of one's thumb movement
- Highly durable and long-wearing
- Insulates better than goatskin or pigskin

#### **Technical Data**

Cowhide
Slip-on-open
Beige
Wing
Heat transfer/Label
7-11
2000 pairs
50-60 days

Performance	EN388:2016: 3121X					
Abrasion	0	1	2	3	4	
Cut	Х	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	Α	В	С	D	Е	F

#### **Applications**

- Agriculture
- Construction
- Engineering
- Industrial works
- Mechanical works
- Oil and Gas
- Warehousing & logistics
- Gardening

Qingdao Snell Protective Products Co., Ltd Dedicated to Security www.snellsafety.com Building B, 36° Impression, 398 Fudong Road, Gaomi, Shandong, China. Tel: +86 17205448906 | sales@snellsafety.com



## T2403 Snell Aramid Palm Leather Cut Resistant Glove



#### **Product Features**

- Cut resistance
- Abrasion resistance
- Heat resistance
- Fire proof
- Heated or sharp objects handling
- Excellent durability

Material	Aramid,kevlar,leather
Cuff	Knitted
Coating	Leather sewing
Coating Coverage	Palm & fingers
Gauge	10
Logo printing	Ink or heat transfer
Sizes	Customized
MOQ	2000 pairs
Production Leadtime	45 days

#### Performance EN388:2016: 3X43D

Abrasion	0	1	2	3	4	
Cut	Х	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	Α	В	С	D	Е	F

#### Applications

- Industry
- Automotive
- Machinery and Equipment
- Metal Fabrication
- Glass industry
- Oil and Gas
- Utilities & logistics
- Warehousing

Qingdao Snell Protective Products Co., Ltd Dedicated to Security www.snellsafety.com Building B, 36° Impression, 398 Fudong Road, Gaomi, Shandong, China. Tel: +86 17205448906 | sales@snellsafety.com



## T2404 Snell Cut Resistant Reinforced Leather Palm Gloves

Technical Data



#### **Product Features**

- Back side open designs the good dexterity and ventilation
- Palm with cowhide leather reinforcement to enhance the abrasion, grip resistance
- Fingernails with extended cowhide leather to protect them safe and anti-smash
- Palm leather stitched prevents heat resistance

Material	HPPE/polyester/leather
Cuff	Knitted
Coating	Leather reinforced
Coating Coverage	Palm & fingers
Gauge	15
Logo printing	Ink or heat transfer
Sizes	10-11
MOQ	3000 pairs
Production Leadtime	50 days

Performance	EN388:2016: 4X43C					
Abrasion	0	1	2	3	4	[
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	Α	В	C	D	Е	F

### Applications

- Steel
- Automotive
- Recycling
- Refuse Industries
- Glass Handling/Manufacture
- Paper and Plastic Industries
- Bakery
- Metal Work



# Qingdao Snell Safety Dedicated to Security

## SPECIFICATION SHEET

12417 Snell Foam Sandy Grip TPR Impact Resistant with Leather Glove



#### **Product Features**

- 15 gauge lycra/nylon blended liner provides excellent dexterity & soft handfeeling.
- Nitrile coated with sandy finishing palm to enhance wet & dry grip.
- TPR molded the back of hand and fingers to make sure maximum safety protection.
- Nitrile thumb saddle reinforcement for extended durability.
- Inner fingers with extra cow leather stitching offers extended durability.

Material	Lycra/nylon
Cuff	Seamless knitting
Coating	Nitrile foam sandy
Coating Coverage	Palm & fingers
Gauge	15
Impact Coverage	Fingers & back of hand
Sizes	7-11
MOQ	8000 pairs
Production Leadtime	45-55 days

Abrasion	0	1	2	3	4	
Cut	Х	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	Α	В	С	D	Е	F

EN388:2016: 4122

### **Applications**

Performance

- Manufacturing
- General Handling
- Auto repair & assembly
- Warehousing
- Picking small parts
- Driving fork lifts and vehicles
- Packing