



SPECIFICATION SHEET

N2414 Snell Nitrile Full Coating Oil Water Repellent Glove



Technical Data

Material	Nylon
Cuff	Seamless knitting
Coating	Nitrile
Coating Coverage	Full hands
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	12000 pairs
Production Leadtime	45 days

Performance

EN388:2016: 4121X

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Seamless knitting with full nitrile coating
- ◆ Super strong resistant to water, oil, fats, grease and liquid
- ◆ Great grip & abrasion resistance
- ◆ Black nitrile color is stain resistant
- ◆ Ideal in wet and oily conditions

Applications

- ◆ Assembly
- ◆ Automotive
- ◆ Construction
- ◆ General handling
- ◆ Industrial work
- ◆ Maintenance
- ◆ Railway maintenance
- ◆ Roofing
- ◆ Transportation
- ◆ Waste Removal



SPECIFICATION SHEET

N2415 Snell Jersey Liner Nitrile Full Dipped Oil Resistant Glove



Technical Data

Material	Jersey liner
Cuff	Knitted
Coating	Nitrile
Coating Coverage	Full hands
Gauge	/
Logo printing	Ink or heat transfer
Sizes	10
MOQ	12000 pairs
Production Leadtime	40 days

Performance

EN388:2016: 2111X

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Jersey cotton lining ensures extremely comfortable fit ideal for general handling
- ◆ Fitted with a knitted wrist to secure the fit and prevent debris from entering glove
- ◆ Nitrile coating ensures excellent mechanical protection
- ◆ High abrasion resistance level makes gloves durable
- ◆ Provides good resistance to oil and greases
- ◆ High levels of grip ideal for handling in wet and oily conditions

Applications

- ◆ General handling
- ◆ Engine manufacture
- ◆ Manufacture
- ◆ Light fabrication
- ◆ Assembly
- ◆ Automotive
- ◆ Construction
- ◆ Local authorities
- ◆ Transport
- ◆ Utilities
- ◆ Warehouse



SPECIFICATION SHEET

N2431 Snell Nitrile Sandy Fully Double Dipped Oil-resistant Glove



Technical Data

Material	Nylon
Cuff	Seamless knitting
Coating	Nitrile sandy
Coating Coverage	Full back+palm
Gauge	13
Logo printing	Ink or heat transfer
Sizes	8-11
MOQ	12000 pairs
Production Leadtime	45 days

Performance

EN388:2016: 4121X

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Lightweight seamless nylon liner
- ◆ Sanding nitrile palm coating for excellent non-slip grip
- ◆ Ideal in wet and oily conditions
- ◆ Food approved, except with acidic foods
- ◆ Advanced abrasion & tear resistance for better performance
- ◆ Outstanding mechanical performance against hand fatigue

Applications

- ◆ Petrochemical
- ◆ Oil platforms
- ◆ Automotive
- ◆ Painting
- ◆ Construction
- ◆ Shipping-maritime
- ◆ Transport and Logistics
- ◆ Manufacturing & engineering
- ◆ Waste management
- ◆ Food processing
- ◆ Maintenance



C2414 Snell Cut Protection Glove for Oily Environments



Technical Data

Material	Hppe/nylon/spandex
Cuff	Seamless knitting
Coating	Sandy nitrile
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	10000 pairs
Production Leadtime	45-55 days

Performance

EN388:2016: 4X43B
ANSI A2

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ 13 gauge seamless liner is lightweight & breathable
- ◆ Double nitrile coating, first with flat nitrile half coated, second with foam nitrile on palm & fingers & thumb makes the high durability
- ◆ The sandy nitrile palm coating is resistant to oils and grease
- ◆ Gives exceptional grip in dry, wet and oily environments.
- ◆ Excellent abrasion and tear properties
- ◆ Withstands contact heat up to 100°C

Applications

- ◆ Automotive
- ◆ Assembly
- ◆ Metal Fabrication
- ◆ Railway Maintenance
- ◆ Construction
- ◆ General Maintenance
- ◆ Machine operating



SPECIFICATION SHEET

C2419 Snell Oil Resistant Half Dipped Safety Glove with Nitrile Foam Sandy



Technical Data

Material	Glass fiber/ polyester
Cuff	Seamless knitting
Coating	Double nitrile
Coating Coverage	Palm & fingers
Gauge	13
Logo printing	Heat transfer
Sizes	7-11
MOQ	8000 pairs
Production Leadtime	45-55 days

Performance

EN388:2016: 4543

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Double coating offers oil & grease resistance.
- ◆ The sandy nitrile coating is resistant to oils and grease.
- ◆ Gives exceptional grip in dry, wet conditions.
- ◆ The comfortable sandy nitrile coating offers maximum abrasion and tear protection.
- ◆ Elasticated cuff for exacting & comfortable fit.

Applications

- ◆ Automotive
- ◆ Component assembly
- ◆ Engineering
- ◆ Construction
- ◆ Utilities
- ◆ Maintenance & repairs
- ◆ Gardening
- ◆ Glass industry



SPECIFICATION SHEET

C2433 Snell Oil Resistant Double Nitrile Coated Cut Glove



Technical Data

Material	Nylon/glass fiber
Cuff	Seamless knitting
Coating	Micro foam nitrile
Coating Coverage	Palm & fingers
Gauge	18
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	10000 pairs
Production Leadtime	45-50 days

Product Features

- ◆ Knit wrist helps prevent dirt and debris from entering the glove
- ◆ 18 gauge nylon with lightweight and good dexterity
- ◆ Double layer coating can prevent the liquid and oil, grease
- ◆ Palm & thumb with black sandy foam nitrile to increase the grip and abrasion resistance
- ◆ Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves

Performance

EN388:2016: 4X42B
ANSI A2

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Applications

- ◆ Automotive
- ◆ Transport
- ◆ Warehousing
- ◆ Logistics
- ◆ Utilities
- ◆ Construction
- ◆ Engineering
- ◆ General Maintenance
- ◆ Waste Management



SPECIFICATION SHEET

C2434 Snell Oil-proof Nitrile Half Coated Cut Protective Glove



Technical Data

Material	Nylon/glass fiber
Cuff	Seamless knitting
Coating	Micro foam nitrile
Coating Coverage	Palm & fingers
Gauge	18
Logo printing	Ink or heat transfer
Sizes	7-11
MOQ	10000 pairs
Production Leadtime	45-50 days

Product Features

- ◆ Knit wrist helps prevent dirt and debris from entering the glove
- ◆ 18 gauge nylon with lightweight and good dexterity
- ◆ Double layer coating can prevent the liquid and oil, grease
- ◆ Palm & thumb with black sandy foam nitrile to increase the grip and abrasion resistance
- ◆ ¾ flat black nitrile coating offers the ventilation for the back when uses

Performance

EN388:2016: 4X42B
ANSI A2

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Applications

- ◆ Automotive
- ◆ Transport
- ◆ Warehousing
- ◆ Logistics
- ◆ Utilities
- ◆ Construction
- ◆ Engineering
- ◆ General Maintenance
- ◆ Waste Management



SPECIFICATION SHEET

N2432 Snell Nitrile Sandy Fully Double Dipped Liquid-resistant Glove



Technical Data

Material	Nylon
Cuff	Seamless knitting
Coating	Nitrile sandy
Coating Coverage	Full back+palm
Gauge	13
Logo printing	Ink or heat transfer
Sizes	8-11
MOQ	12000 pairs
Production Leadtime	45 days

Performance

EN388:2016: 4121X

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Lightweight seamless nylon liner
- ◆ Sanding nitrile palm coating for excellent non-slip grip
- ◆ Ideal in wet and oily conditions
- ◆ Food approved, except with acidic foods
- ◆ Advanced abrasion & tear resistance for better performance
- ◆ Outstanding mechanical performance against hand fatigue

Applications

- ◆ Petrochemical
- ◆ Oil platforms
- ◆ Automotive
- ◆ Painting
- ◆ Construction
- ◆ Shipping-maritime
- ◆ Transport and Logistics
- ◆ Manufacturing & engineering
- ◆ Waste management
- ◆ Food processing
- ◆ Maintenance



SPECIFICATION SHEET

N2504 Snell Jersey Liner Nitrile Safety Cuff Oil Resistant Glove



Technical Data

	Jersey liner
Cuff	Safety
Coating	Nitrile
Coating Coverage	Full hands
Gauge	/
Logo printing	Ink or heat transfer
Sizes	10
MOQ	12000 pairs
Production Leadtime	40 days

Performance

EN388:2016: 4111X

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Product Features

- ◆ Features a full nitrile coating that offers grip, protection and comfort
- ◆ Fitted with a safety cuff that provides additional protection
- ◆ Excellent abrasion resistance means gloves are highly durable
- ◆ Fitted with a cotton inner liner that provides long-lasting comfort
- ◆ Full nitrile coating offers oil and grease resistant

Applications

- ◆ Automotive
- ◆ Builders
- ◆ Cargo handling
- ◆ Construction
- ◆ Engineering
- ◆ General handling
- ◆ Maintenance
- ◆ Mechanics
- ◆ Oil handling
- ◆ Packaging
- ◆ Railway maintenance
- ◆ Scaffolding
- ◆ Warehouse