



**T2501 Snell Uncoated Cut Resistant Protective Glove**



**Technical Data**

|                     |                      |
|---------------------|----------------------|
| Material            | HPPE/polyester       |
| Cuff                | Seamless Knitting    |
| Coating             | No                   |
| Coating Coverage    | No                   |
| Gauge               | 13                   |
| Logo printing       | Ink or heat transfer |
| Sizes               | Customized           |
| MOQ                 | 12000 pairs          |
| Production Leadtime | 40 days              |

**Performance**

EN388:2016: XXXXB

|               |   |          |   |   |   |   |
|---------------|---|----------|---|---|---|---|
| Abrasion      | 0 | 1        | 2 | 3 | 4 |   |
| Cut           | X | 1        | 2 | 3 | 4 | 5 |
| Tear          | 0 | 1        | 2 | 3 | 4 |   |
| Puncture      | 0 | 1        | 2 | 3 | 4 |   |
| Cut (TDM-100) | A | <b>B</b> | C | D | E | F |

**Product Features**

- ◆ 13 gauge liner with seamless knitting construction designs excellent dexterity
- ◆ HPPE and polyester blended offers cut resistance function
- ◆ Uncoating on the gloves offers good ventilation & dexterity

**Applications**

- ◆ Industrial work
- ◆ Food
- ◆ Handling
- ◆ Machinery
- ◆ Equipment
- ◆ Gardening work
- ◆ Warehousing
- ◆ Logistics
- ◆ Packing work