



SPECIFICATION SHEET

T2513 Snell TPE Injection Anti Vibration Abrasion Safety Glove



Technical Data

Material	Polyester
Cuff	Seamless knitting
Coating	TPE
Coating Coverage	Palm & fingers
Gauge	13
Sizes	8-11
MOQ	3000 pairs
Production Leadtime	45-50 days

Product Features

- ◆ 13 gauge seamless knitting instruction makes the glove with good dexterity
- ◆ Palm coated the TPE injection to enhance the grip, abrasion resistance
- ◆ The TPE material with excellent oil-proof, water repellent function, which is suitable for the automotive and maintenance industry
- ◆ The special coating can be used in wet and dry working conditions, keeps the great grip
- ◆ Anti-smash, anti-static, oil-resistant, liquid-resistant, anti-slip

Performance

EN388:2016: 4131

Abrasion	0	1	2	3	4	
Cut	X	1	2	3	4	5
Tear	0	1	2	3	4	
Puncture	0	1	2	3	4	
Cut (TDM-100)	A	B	C	D	E	F

Applications

- ◆ Auto repair & assembly
- ◆ Gardening
- ◆ Painting
- ◆ Furniture manufacturing
- ◆ Machinery
- ◆ Warehousing
- ◆ Equipment maintenance & repair
- ◆ Polishing
- ◆ Road construction